

Model

LS50 Wireless II

Drive Units

Uni-Q Driver Array:
LF: 130 mm (5.25 in.) aluminium conus HF: 25 mm (1 in.) vented aluminium dome met Metamaterial Absorption Technology

FREQUENTIEBEREIK (-6DB) GEMETEN BIJ: 85DB/1M

40 Hz – 47 kHz
*Afhankelijk van EQ settings

FREQUENCY RESPONSE (±3DB) MEASURED AT 85DB/1M

45 Hz – 28 kHz
*Afhankelijk van EQ settings

VERSTERKER OUTPUT POWER (PER SPEAKER)

LF: 280W
HF: 100W

VERSTERKER KLASSE (PER SPEAKER)

LF: Class D
HF: Class AB

MAX SPL GEMETEN OP 1M

108 dB

WIRELESS STREAMING OPTIES

AirPlay 2
Google Chromecast
ROON Ready
UPnP
Bluetooth 4.2

SOURCE RESOLUTIE

Network tot 384kHz/24bit
Optical tot 96kHz/24bit
Coaxial tot 192kHz/24bit
HDMI tot 192kHz/24bit

*Afhankelijk van source resolutie

INTERSPEAKER CONNECTIE

Wireless: alle sources resampled tot 96kHz/24bit PCM

Wired: alle sources resampled tot 192kHz/24bit PCM

ONDERSTEUNDE FORMATS (ALL INPUTS)

MP3, M4A, AAC, FLAC, WAV, AIFF, ALAC, WMA, LPCM and Ogg Vorbis

SUPPORTED FORMAT (NETWORK)

MQA
DSF: DSD64, DSD128
DFF: DSD64

AFMETINGEN (HWD PER SPEAKER)

305 x 200 x 311 mm (12 x 7.9 x 12.2 in.)

GEWICHT (PER SET)

20.1kg (44.31lbs)

POWER INPUT

100 – 240VAC 50/60Hz

POWER CONSUMPTIE

200W (operationeel)
<2.0W (standby)

STREAMING SERVICES

Spotify via Spotify Connect
Tidal via Tidal Connect
Amazon Music
Qobuz
Deezer
QQ Music via QPlay (binnenkort beschikbaar)
Internet Radio
Podcast

*Servicebeschikbaarheid kan per land verschillen

PRIMAIRE SPEAKER INPUTS

HDMI eARC
TOSLINK Optisch
Digital Coaxiaal
Analog 3.5mm Aux
USB Type A (service)
RJ45 Ethernet (netwerk)
RJ45 Ethernet (interspeaker)

OUTPUT

RCA Subwoofer output

WI-FI NETWORK STANDAARD

IEEE 802.11a/b/g/n/ac IPv4, IPv6

WI-FI NETWORK FREQUENTIE BAND

Dual-band 2.4 GHz / 5 GHz

SECUNDAIRE SPEAKER INPUTS

USB Type A (service) RJ45 Ethernet (interspeaker)